



ELECTRODEPOT

Contactor, IEC,

120VAC, 3P, 32A

Part # 933210

- Rated Operational Current : 32A;lth : 50A;Ui : 660V

Technical Specifications

- Contactor 660V
- Contactor Type IEC
- Full Load Amps-Inductive 32
- Full Load Amps-Resistive 50
- Number of Poles 3
- Coil Volts 120VAC
- Hz 50/60
- Action Non reversing
- Enclosure Type Open
- Auxiliary Contact Form 1NC/1NO
- Coil inrush 70VA, Sealed 7.5VA
- 2 HP @ 1 Phase - 120V
- 5 HP @ 1 Phase - 230V
- 10 HP @ 3 Phase - 208V
- 10 HP @ 3 Phase - 230V
- 20 HP @ 3 Phase - 480V
- 30 HP @ 3 Phase - 575V
- Height 3.50"
- Width 2.22"
- Depth 3.50"
- Standards CE,
- Base or DIN 35mm mount

Wiring:

Solid Conductor: 25 mm² Max torque 0.6 Nm

Stranding Conductor: 16 mm², Max torque 0.6 Nm

Compliance with the following standards:

EN 60947-4-1, EN 60947-5-1, IEC 947-2, IEC 60947-4-1, IEC 60947-5-1, UL 508, VDE 0660